



Contract Numbers:  
GM - #706-23  
CE - #685-22

SVL97-2HFC WEB QUOTE #2703006

Date: 8/23/2023 5:44:29 AM

- Customer Information -

County, Panola

Panola County Road and Bridge

melanie.earle@co.panola.tx.us

903-693-0375

Quote Provided By  
LOWE TRACTOR & EQUIPMENT, INC.  
Kyle Keeling  
2213 STATE HIGHWAY 64 W  
HENDERSON, TX 75653  
email: kyle@lowetractor.com  
phone: 9036573538

- Standard Features -

- Custom Options -



**Kubota**

S Series

SVL97-2HFC

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

**FEATURES**

Final Tier 4 Certified Kubota Diesel Engine  
Electronic Travel Torque Management System  
Vertical Lift Path Loader Frame  
Standard Front Quick Coupler, Float Standard  
Hydraulic Quick Coupler Option  
Loader Arm Self-Leveling  
Loader Boom Lock  
Open ROPS/FOPS  
Optional enclosed and pressurized cab with A/C  
High Back, Adjustable, Vinyl, Suspension Seat  
2" Retractable Seat Belt And 2-Piece Seat Bar  
23.1 gpm Auxiliary Hydraulics  
Standard, 40.0 gpm Option  
Case Drain Line  
Rigid Mounted Undercarriage, 5 Lower Track Rollers  
High Grip Rubber Tracks, 17.7" Standard  
Two Speed Travel System  
Automatic Wet Disk Parking Brake  
Kubota 4 Hydraulic Pump Load Sensing System  
2 Variable Displacement Pumps  
Rearview Camera  
KubotaNOW Telematics  
Lockable DEF Cap Guard  
Hydraulic Joystick Controls  
ISO Operating Pattern  
Dial Knob and Foot Throttle Controls  
Stall Guard Engine Controls  
Automatic Glow Plugs  
Key Switch Stop System  
Self Bleed Fuel System  
2 Front and 2 Rear Working Lights  
Hour Meter, Engine Temperatur, DEF, and Fuel Gauges and Warning Lights  
Lockable DEF Tank Cap  
Lockable Fuel Cap  
Radio Ready on Enclosed Cabs

**BASIC UNITS**

SVL97-2S, 17.7" Rubber Tracks, Open ROPS/FOPS Cab  
Quick Coupler

**OPERATIONAL DIMENSIONS**

Operating Weight\*, SVL97-2s, 17.7" Rubber Tracks, Open ROPS/FOPS Cab, Mechanical Quick Coupler 11,299 lbs.  
Rated Operating Capacity (ROC) @ 35% of Tipping Load complies with ISO 14397-1 and SAE J 818) 3,200 lbs.  
Rated Operating Capacity (ROC) @ 50% of Tipping Load 4,572 lbs.  
Tipping Load 9,143 lbs.  
Auxiliary Hydraulics Flow 24 / 40.0 gpm  
Travel Speed (Low / High) 5.0 / 7.3 mph  
Reach @ Maximum Height 40.7"  
Height to Hinge Pin 128.6"  
Ground Pressure 4.5 psi.  
Traction Force 12,178 lbf.

\* Includes operator's weight, 175 lbs.

**ENGINE**

V3800-Tier 4 Kubota Final Tier 4 Diesel Engine  
4 Cylinder, 4 Cycle, Turbo Charged  
96.0 Gross HP @ 2400 rpm

**DIMENSIONS**

Cab Height 83.4"  
Width (without attachment) 77.2"  
Length (without attachment) 123.5"  
Length of Track on Ground 65.6"

SVL97-2HFC Base Price: \$91,154.00

(1) SVL REAR VIEW CAMERA KIT S6780-SVL REAR VIEW CAMERA KIT inc.  
(1) SVL TELEMATICS HARNESS S6702-SVL TELEMATICS HARNESS inc.  
(1) AT&T TELEMATICS MODEM DCU6700-AT&T TELEMATICS MODEM inc.  
(1) 80" LPLF BKT W/BOCE/BOSC/SVL90 S6605-80" LPLF BKT W/BOCE/BOSC/SVL90 \$2,675.00  
**Configured Price: \$93,829.00**  
BUY BOARD Discount: (\$22,518.96)  
**SUBTOTAL: \$71,310.04**  
Dealer Assembly: \$0.00  
Freight Cost: \$831.25  
PDI: \$400.00

Total Unit Price: \$72,541.29  
Quantity Ordered: 1  
Final Sales Price: \$72,541.29

**Purchase Order Must Reflect the Final Sales Price**

To order equipment - purchase orders must be made out and returned to:

Kubota Tractor Corporation  
Attn: National Accounts  
1000 Kubota Drive  
Grapevine, TX 76051  
or email NA.Support@kubota.com  
or call 817-756-1171 or fax 844-582-1581

*Rodger S. McLane*

\*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.